

INDUSTRIAL FLOOD LIGHT SERIES

High-performance flood lights designed for industrial and commercial applications. Built to deliver maximum brightness, durability and reliability.



WIDE BEAM COVERAGE

Large illumination area for maximum visibility.



LONG DISTANCE LIGHTING

High-performance PC lens, lighting distance over 30M.



EXTREME TEMPERATURE

Working temperature: -30°C to 50°C.



360° ADJUSTABLE BRACKET

Flexible angle adjustment, easy and convenient.



IP67 WATERPROOF

Reliable performance in harsh outdoor conditions.



ULTRA-THIN DESIGN

Ultra-thin design to save shipping costs.



SURGE & LIGHTNING PROTECTION

5000V surge protection and advanced lightning protection.



DIE-CAST ALUMINUM BODY

Ultra-thin design, strong, durable and cost-saving.



ANTI-FOG BREATHING VALVE

Prevent condensation and keep the lens clear.



HIGH BRIGHTNESS OUTPUT

Stable high brightness output, suitable for wide applications.



WAREHOUSE



FACTORY



STADIUM



PORT



COLD STORAGE



INDUSTRIAL FLOOD LIGHT SERIES

Professional Outdoor Lighting Solutions
For Industrial & Commercial Applications



INDUSTRIAL FLOOD LIGHT SERIES

Professional Outdoor Lighting Solutions
For Industrial & Commercial Applications



PRODUCT OVERVIEW

FLOODLIGHT SERIES

BRIVOLUXTECH

Engineered for industrial and commercial environments, our Floodlight Series delivers powerful, reliable illumination, with outstanding energy efficiency and long-term durability. Ideal for large-scale outdoor applications.



MODEL	LED QTY (PCS)	MATERIAL	LUMEN (LM)	INPUT VOLTAGE (V)	COLOR TEMP (CCT)	CRI (RA)	POWER (W)	NET WEIGHT (N.W)	GROSS WEIGHT (G.W)	COLOR BOX SIZE (CM)	CARTON SIZE (CM)	PACKING (PCS/CTN)
BLT-FLHS50	70	PC Lens + Die-cast Aluminum Housing	6500lm±5%	110~265V	6500k±5%	≥80	50W±5%	13.5Kg	11.5Kg	24*3.3*18	35*25.5*38	20PCS
BLT-FLHS100	140	PC Lens + Die-cast Aluminum Housing	13500lm±5%	110~265V	6500k±5%	≥80	100W±5%	8.5Kg	9.8Kg	27.5*3.5*21.2	37*29*23	10PCS
BLT-FLHS200	252	PC Lens + Die-cast Aluminum Housing	24000lm±5%	110~265V	6500k±5%	≥80	180W±5%	7.5Kg	9Kg	33*4*26.1	34.5*22*27.5	5PCS
BLT-FLHS300	350	PC Lens + Die-cast Aluminum Housing	36000lm±5%	110~265V	6500k±5%	≥80	250W±5%	11.5Kg	10Kg	36.3*4.3*28.5	38*23.5*31	5PCS
BLT-FLHS400	440	PC Lens + Die-cast Aluminum Housing	44600lm±5%	110~265V	6500k±5%	≥80	350W±5%	8.7Kg	9.6Kg	42*4.3*34	43.5*14.5*36	3PCS
BLT-FLHS600	588	PC Lens + Die-cast Aluminum Housing	59800lm±5%	110~265V	6500k±5%	≥80	450W±5%	9.9Kg	10.8Kg	46*4.5*45	47.5*15*37	3PCS



HIGH EFFICIENCY
Up to 150lm/W system efficacy.



HIGH CRI
CRI ≥80 for true color performance.



SURGE PROTECTION
5000V protection for enhanced reliability.



WIDE VOLTAGE
110-265V wide voltage input.



DURABLE BUILD
Aluminum body with excellent heat dissipation.



FLEXIBLE INSTALLATION
Adjustable bracket for multiple mounting options.



IP67 RATING
Dustproof and waterproof for harsh conditions.



LONG LIFESPAN
50,000 hours lifespan for lower maintenance.



WIDE APPLICATION
Ideal for industrial, commercial, stadium, port, and more.

* The above data is for reference only. Please refer to actual products for final information.